

ROBUST DESIGN AND CONSTRUCTION,
PERFECT FOR PORTABLE RENTAL SOLUTIONS

VM RENTAL RANGE

RATING: 30 kVA - 350 kVA

JUST SOME OF THE GREAT FEATURES:

- Stage 3A Emission Compliant Engines
- Stamford Alternators
- Deep Sea Controllers
- Class-leading Noise Levels
- RFID Tag Chip
- 50/60Hz Switching

TEL: 01724 710010
www.suttonpower.co.uk



We are proud to be the UK partners of





IVECO RANGE

Model	Continuous Output kVA	Continuous Rating Output kW	Engine Rating	Engine	Electronic Stage	Alternator Reg	Fuel Tank Size	Dimensions			Dry Weight (kg)	dBA@ 7M
								Width (mm)	Length (mm)	Height (mm)		
F33	30	24	Iveco	III	Option	Stamford	250	1130	2420	1600	1450	63
F63	60	48	Iveco	III	Option	Stamford	480	1130	2970	1870	1810	62
F83	80	66.4	Iveco	III	Yes	Stamford	480	1130	2970	1870	1990	64
F103	100	80	Iveco	III	Yes	Stamford	480	1130	2970	1870	2010	64
F133	140	104	Iveco	III	Option	Stamford	850	1140	3680	2320	2760	65
F153	150	120	Iveco	III	Yes	Stamford	850	1140	3680	2320	2980	65
F203	200	160	Iveco	III	Yes	Stamford	850	1140	3680	2320	3010	67
F253	250	200	Iveco	III	Yes	Stamford	850	1200	4340	2500	4200	69
F303	300	240	Iveco	III	Yes	Stamford	850	1200	4340	2500	4350	69
F353	350	280	Iveco	III	Yes	Stamford	850	1200	4340	2500	4350	69

JOHN DEERE RANGE

JD43	40	32	John Deere	III	N/A	Stamford	250	1130	2420	1600	1560	63
------	----	----	------------	-----	-----	----------	-----	------	------	------	------	----



STANDARD

- Guard Touch Automatic Controller AMF
- 4 Pole Breaker with Earth Leakage Protection
- Extended Bus Bar Connections
- Earth Fault Relay
- Optima Gel Battery
- 3 Way Fuel Valves
- Battery Isolator Switch
- CE Certification
- Central Lifting Point (RUD) Product
- Air Inlet with Rain/Sand Protection
- Rain gutters above doors to prevent water ingress
- Adjustable Cam latches with locable handles
- Heavy Duty / Durable sound insulation material
- Heavy Duty Galvanised Canopy

FREE OPTION

- Fork Lift Pockets
- Radiator Access Door
- Fuel Tank Port Holes
- Internal Fueling Point
- Fuel Tank retention Base with Sensor
- Engine Oil Drain Pump
- Low coolant sensor
- Standard Socket Configuration
- Deep Sea 7320 AMF Controller
- Comap AMF 25 Controller
- Marelli Alternator
- Alternator Protection

COST OPTION

- PMG (Permanent Magnet Generator)
- Murphy Lube Level
- Bypass switch for adjustable RCD
- 50/60Hz Selector Switch
- Racor Fuel Filter
- Engine Water Pre Heater
- Metal Bumper Protection
- Custom Colour (Yellow/White are Standard)
- Central Lifting Point with RFID
- Battery Charger
- Custom Socket Configuration
- Motorised Breaker
- Comap Intellivision 5 Synchronised Controller
- Deep Sea 8610 Synchronised Controller